



BEE GREEN ATF D/M III

BeeGreen™ ATF is a premium transmission fluid designed and recommended for use in automatic transmissions previously serviceable by GM DEXRON®-III (H) and Ford MERCON® brands. It may also be used in equipment requiring a “Type A” ATF fluid, Allison C-4, Caterpillar TO-2, and Ford specifications M2C138-CJ and M2C166-H.

BeeGreen™ ATF is formulated to provide:

- Superior wear protection.
- Excellent frictional properties for smooth shifting.
- Excellent anti-shudder performance.
- Good seal compatibility.
- Protection against varnish and sludge formation.
- Superior thermal stability and oxidation resistance.
- Outstanding low-temperature performance.

BeeGreen™ ATF’s state-of-the-art additive system provides ultimate protection and peak performance in passenger cars, SUV’s and light trucks. BeeGreen™ ATF is not recommended for use in transmissions requiring GM DEXRON®-VI, Ford MERCON®-V and MERCON® SP fluids.

BeeGreen™ ATF also makes an excellent hydraulic fluid in mobile or industrial applications where low temperature fluidity or leak detection is an important consideration.



BeeGreen™ ATF D/M III

TYPICAL INSPECTION TESTS

Density, g/cm ³ @ 15° C	0.860
Flash Point, COC C° (F°)	212 (413)
Viscosity, cP @ -20° C	1300
Viscosity, cP @ -30° C	4200
Viscosity, cP @ -40° C	17000
Viscosity, cSt @ 40° C	35.4
Viscosity, cSt @ 100° C	7.2
Viscosity Index	172
Pour Point, C° (F°)	-52 (-61)
Color	Red
Foam Test, ASTM D892	Pass