



HYDRAULIC AW OILS

BeeGreen™ Hydraulic AW Oils are premium hydraulic fluids formulated from premium re-refined base stocks and select additives to deliver ultimate equipment protection. They offer a unique combination of optimum protection and the conservation of irreplaceable petroleum resources.

BeeGreen™ Hydraulic AW Oils are excellent anti-wear oils containing anti-oxidation, anti-corrosion, anti-rust and anti-foam agents. These superior characteristics protect pumps, lines and controls against rust and corrosion. They also exhibit excellent demulsification (water separation) properties, even at high operating temperatures.

BeeGreen™ Hydraulic AW Oils deliver performance equal to greater than conventional lubricants. They are recommended for hydraulic systems, high-pressure circulating systems, and are suitable for use where the following requirements are recommended:

- Denison Parker HF-0, HF-1 & HF-2
- Eaton Vickers M-2950-S I-286-S
- Cincinnati Lamb P-68, P-69 & P-70
- DIN 51524 (Part II, III) (2006)
- ANSI/AGMA 9005-E02-RO
- ASTM D 6158 (HM, HV)
- ISO 11158 (HM, HV)
- GM LS-2
- JCMAS P041 (HK)
- AIST 126, 127
- Bosch RE 90 220
- SEB 181222 (FZG 12 has been met in most base oils)
- SAE MS 1004 (HM,HV)



BeeGreen™ Supreme Motor Oils

TYPICAL INSPECTION TESTS

ISO Grade	32	46
Lbs./Gallon	7.2	7.2
Pour Point °C	-27	-22
FlashPoint, °C	200	200
Oxidation Hrs, ASTM D-943	>2500	>2500
Viscosity Index	101	101
Viscosity, cSt @ 40° C	32.0	45.8
Viscosity, cSt @ 100 °C	5.6	6.9
Gravity, API	30.4	31.8